

Example

# BPM Masters

<b>by:</b>	Alex del Bondio
<b>published:</b>	October 2017
<b>description:</b>	Macros for double, half, tap, reset each of the BPM masters.
<b>remarks:</b>	This is based on the <a href="#">fixed Titan IDs</a> which we found exactly for these macros. <a href="#">[ , BPM, master, double, half, speed, tap, tempo, ]</a>

## functions

- [Masters.DoubleOrHalfSpeedMultiplier](#)
- [Masters.TapTempo](#)
- [Math.GetCurrentTimeStamp](#)
- [Masters.ResetSpeedMultiplier](#)

The file

`adb_bpmmaster.xml`

has the macros already written for all 4 BPM masters. Here, we use BPM master 1 to explain it.

## Code

`bpmmasters.xml`

```
<?xml version="1.0" encoding="utf-8"?>
<avolites.macros xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="Avolites.Menus.xsd">
  <macro id="Avolites.Macros.BPM1half" name="adb_BPM1 /2">
    <sequence>
      <step>Masters.DoubleOrHalfSpeedMultiplier(1607,false)</step>
    </sequence>
  </macro>

  <macro id="Avolites.Macros.BPM1tap" name="adb_BPM1 tap">
    <sequence>
      <step>Masters.TapTempo(1607, Math.GetCurrentTimeStamp())</step>
    </sequence>
  </macro>

  <macro id="Avolites.Macros.BPM1double" name="adb_BPM1 *2">
    <sequence>
      <step>Masters.DoubleOrHalfSpeedMultiplier(1607,true)</step>
    </sequence>
  </macro>

  <macro id="Avolites.Macros.BPM1*1" name="adb_BPM1 *1">
```

```
<sequence>  
  <step>Masters.ResetSpeedMultiplier(1607)</step>  
</sequence>  
</macro>  
</avolites.macros>
```

## Explanation

This explains the functional steps within the sequence. For all the other XML details please refer to [Formats and syntax](#)

- `Masters.DoubleOrHalfSpeedMultiplier(1607, false)` halves the bpm speed of bpm master 1 which is identified by its fixed titan ID
- `Masters.DoubleOrHalfSpeedMultiplier(1607, true)` doubles the bpm speed of bpm master 1 which is identified by its fixed titan ID
- `Masters.TapTempo(1607, Math.GetCurrentTimeStamp())` taps the bpm speed of bpm master 1 which is identified by its fixed titan ID. The timestamp is a required parameter for this function to work, see [Masters.TapTempo](#)
- `Masters.ResetSpeedMultiplier(1607)` resets the bpm speed of bpm master 1 which is identified by its fixed titan ID

## How to use it

1. [make this macro available](#)
2. apply when needed (you'll see the results when you have BPM masters assigned)

From:  
<https://www.avosupport.de/wiki/> - **AVOSUPPORT**

Permanent link:  
<https://www.avosupport.de/wiki/macros/example/bpmmasters?rev=1512561298>

Last update: **2017/12/06 11:54**

