

Example

# Chase - Change a chaser's overlap

<b>by:</b>	Gregory Haynes, Ricster, Apr. 2017
<b>published:</b>	<a href="http://forum.avolites.com/viewtopic.php?f=20&amp;t=5150">http://forum.avolites.com/viewtopic.php?f=20&amp;t=5150</a>
<b>description:</b>	snippets to change a chaser's overlap
<b>remarks:</b>	not a working macro but interesting discussion and insights on some properties, types, and type casting

Chase, X-fade, handle

## functions

- ActionScript SetProperty
- ActionScript SetProperty.Float
- Math.Cast.ToSingle

## affected properties

- Playbacks.Editor.SelectedPlayback
- Chases.ConnectedHandle
- Playbacks.Editor.Times.ChaseFixtureOverlap

## Code

```
<macro id="UserMacro.SetChaseOverlap50" name="Set Chase Overlap 50%">
  <description>Set fixture overlap of connected chase to 50%.</description>
  <sequence>
    <step>ActionScript SetProperty("Playbacks.Editor.SelectedPlayback",
Chases.ConnectedHandle)</step>
    <step>ActionScript SetProperty.Float("Playbacks.Editor.Times.ChaseFixtureOverlap",
0.5)</step>
  </sequence>
</macro>
```

```
<!-- Ricster's reply: -->
<step>ActionScript SetProperty("Playbacks.Editor.Times.ChaseFixtureOverlap",
Math.Cast.ToSingle(1))</step>
```

```
<!--
  Might also work.
  Or even
-->
```

```
<step>ActionScript SetProperty.Float("Playbacks.Editor.Times.ChaseFixtureOverlap",
1)</step>
```

```
<!-- And as of 10.1 I think you can do -->
```

```
<step>ActionScript SetProperty("Playbacks.Editor.Times.ChaseFixtureOverlap",  
float:1)</step>
```

## Explanation

This explains the functional steps within the sequence. For all the other XML details please refer to [Formats and syntax](#)

- ActionScript SetProperty("Playbacks.Editor.SelectedPlayback", Chases.ConnectedHandle) makes the currently connected handle active in the editor
- ActionScript SetProperty.Float("Playbacks.Editor.Times.ChaseFixtureOverlap", 0.5) sets the property "Playbacks.Editor.Times.ChaseFixtureOverlap" to 0.5 which is 50%

Another example was published by kimwida: <http://forum.avolites.com/viewtopic.php?f=20&t=5579> where the chasers are referred by their usernumber and a legend is set to reflect the current overlap value:

```
<step  
pause="0.01">ActionScript SetProperty("Playbacks.Editor.SelectedPlayback",  
handle:"chaseHandleUN=19159")</step>  
  <step  
pause="0.01">ActionScript SetProperty("Playbacks.Editor.Times.ChaseFixtureOverlap", 0.2)</step>  
  <step  
pause="0.01">ActionScript SetProperty("Playbacks.Editor.SelectedPlayback",  
handle:"chaseHandleUN=19160")</step>  
  <step  
pause="0.01">ActionScript SetProperty("Playbacks.Editor.Times.ChaseFixtureOverlap", 0.2)</step>  
  <step  
pause="0.01">Handles.SetSourceHandleFromHandle("chaseHandleUN=1293")</step>  
    <step pause="0.01">ActionScript SetProperty("Handles.PendingLegend",  
"Overlap 20%")</step>  
    <step pause="0.01">Handles.SetLegend()</step>  
    <step pause="0.01">Handles.ClearSelection()</step>
```

## How to use it

1. [make this macro available](#)
2. once a chase is active and connected, fire this macro to set the chaser to 50% crossfade

From:  
<https://www.avosupport.de/wiki/> - **AVOSUPPORT**



Permanent link:  
<https://www.avosupport.de/wiki/macros/example/changechaseroverlap>

Last update: **2019/04/27 19:11**