

Example

# ClearColour

<b>by:</b>	
<b>published:</b>	October 2017
<b>description:</b>	Clears Colour from programmer
<b>remarks:</b>	Example for usage of <a href="#">clear mask</a>

[, [clear](#), [attribute](#), [programmer](#), [editor](#), [colour](#), [mask](#), ]

## functions

- [Programmer.Editor.Clear](#)

## Code

[clearcolour.xml](#)

```
<?xml version="1.0" encoding="utf-8"?>
<avolites.macros xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="Avolites.Menus.xsd">
  <macro id="ClearColour" name="ClearColour">
    <sequence>
      <!-- Clear mask is the first argument Intensity=1,
Positions=2,Colours=4, Gobos=8, Beam=16, Effect = 32, Special = 64, FX
= 128, Time = 256 -->
      <!-- (int Mask, bool Clear Presets, bool ClearAllProgrammers, float
fadeTime) -->
      <step pause="0.01">Programmer.Editor.Clear(4, true, false,
0)</step>
    </sequence>
  </macro>
</avolites.macros>
```

## Explanation

This explains the functional steps within the sequence. For all the other XML details please refer to [Formats and syntax](#)

Simply calls `Programmer.Editor.Clear` with the correct parameters.

## How to use it

- [make this macro available](#)
- instead of holding <Clear> and setting the clear mask you can now fire this macro in order to clear only colour.

From:

<https://www.avosupport.de/wiki/> - **AVOSUPPORT**

Permanent link:

<https://www.avosupport.de/wiki/macros/example/clearcolour?rev=1511888030>

Last update: **2017/11/28 16:53**

