

Example

# Cuelist - Go back

<b>by:</b>	Gregory Haynes, Jul. 2017
<b>published:</b>	<a href="http://forum.avolites.com/viewtopic.php?f=20&amp;t=5274">http://forum.avolites.com/viewtopic.php?f=20&amp;t=5274</a>
<b>description:</b>	makes a specific cuelist go back
<b>remarks:</b>	snippet which explains CueLists.GoBack(Handle handle)

[cuelist](#), [go back](#), [handle](#), [location](#)

## functions

- [CueLists.GoBack](#)

## Code

```
<step>CueLists.GoBack("Location=Playbacks,2,1")</step>
```

## Explanation

This explains the functional steps within the sequence. For all the other XML details please refer to [Formats and syntax](#)

This simply calls the function `CueLists.GoBack()` with a designated handle as argument. The handle "Location=Playbacks,2,1" translates to 'Playbacks, page 2, 1st playback' - this is the 'real' fader playbacks (see [Identifiers](#)). *tested - S. Beutel*

## How to use it

This is an example oneliner - you need to pack it into a macro file before you can use it in Titan. Example to be used in your own macros.

From: <https://www.avosupport.de/wiki/> - AVOSUPPORT

Permanent link: <https://www.avosupport.de/wiki/macros/example/cuelistgoback?rev=1556364284>

Last update: 2019/04/27 11:24

