

Example

# Cuelist - Set Option FireFirstCue

<b>by:</b>	Sebastian Beutel, June 2021
<b>published:</b>	here
<b>description:</b>	Set some Cuelists' option to Fire First Cue on/off
<b>remarks:</b>	with kind support by Gregory Haynes

[cuelist](#), [set](#), [option](#), [range](#), [fire](#), [first](#)

## functions

- [someusedfunction](#)
- [anotherusedfunction](#)
- [someusedfunction](#)
- [anotherusedfunction](#)

## affected properties

- [someproperty](#)
- [anotherusedproperty](#)

## control structures

- [step condition](#)

## Code

[SetCuelistOptionFFQ.xml](#)

```
<?xml version="1.0" encoding="utf-8"?>
<avolites.macros>

<!-- Macros to set a cuelists options to fire first cue -->
<!-- Sebastian Beutel, June 2021 -->
<!-- xxx macros are used within the macros further down -->

  <macro id="Wiki.Macros.Cuelists.SetOption.FFQ.On" name="xxx Set PB
option to FFQ On">
    <sequence>
      <step pause="0.05">Handles.FilterHandleOptions()</step>
      <step
pause="0.05">ActionScript.SetProperty.Boolean("HandleOptions.CueLists.F
ireFirstCue",true)</step>
      <step pause="0.05">Handles.ClearSelection()</step>
      <step pause="0.05">Handles.ClearHandleOptionsFilter()</step>
```

```
</sequence>
</macro>

<macro id="Wiki.Macros.Cuelists.SetOption.FFQ.Off" name="xxx Set PB
option to FFQ Off">
  <sequence>
    <step pause="0.05">Handles.FilterHandleOptions()</step>
    <step
pause="0.05">ActionScript.SetProperty.Boolean("HandleOptions.CueLists.F
ireFirstCue", false)</step>
    <step pause="0.05">Handles.ClearSelection()</step>
    <step pause="0.05">Handles.ClearHandleOptionsFilter()</step>
  </sequence>
</macro>

<!-- these macros reference the xxx macros above -->

<macro id="Wiki.Macros.Cuelists.SetOption.FFQ1.On" name="Set CL 101
to FFQ On">
  <sequence>
    <step
pause="0.05">Handles.SetSourceHandleFromHandle("playbackHandleUN=101")<
/step>
    <step
pause="0.05">UserMacros.RecallMacroById("Wiki.Macros.Cuelists.SetOption
.FFQ.On")</step>
  </sequence>
</macro>

<macro id="Wiki.Macros.Cuelists.SetOption.FFQ1.Off" name="Set CL 101
to FFQ Off">
  <sequence>
    <step
pause="0.05">Handles.SetSourceHandleFromHandle("playbackHandleUN=101")<
/step>
    <step
pause="0.05">UserMacros.RecallMacroById("Wiki.Macros.Cuelists.SetOption
.FFQ.Off")</step>
  </sequence>
</macro>

<!-- setting the option for a range works only if the first in the
range needs to be changed -->
<!-- that's why here it is set the other way before the range is set as
intended -->

<macro id="Wiki.Macros.Cuelists.SetOption.FFQ1thro4.On" name="Set PB
thro 4 to FFQ On">
  <sequence>
    <step pause="0.05">Handles.SetSourceHandle("Playbacks", 0)</step>
```

```

    <step
pause="0.05">UserMacros.RecallMacroById("Wiki.Macros.Cuelists.SetOption
.FFQ.0ff")</step>
    <step pause="0.05">Handles.SetSourceHandleRange("Playbacks", {0,
1, 2, 3})</step>
    <step
pause="0.05">UserMacros.RecallMacroById("Wiki.Macros.Cuelists.SetOption
.FFQ.0n")</step>
  </sequence>
</macro>

<macro id="Wiki.Macros.Cuelists.SetOption.FFQ1thro4.0ff" name="Set PB
thro 4 to FFQ 0ff">
  <sequence>
    <step pause="0.05">Handles.SetSourceHandle("Playbacks", 0)</step>
    <step
pause="0.05">UserMacros.RecallMacroById("Wiki.Macros.Cuelists.SetOption
.FFQ.0n")</step>
    <step pause="0.05">Handles.SetSourceHandleRange("Playbacks", {0,
1, 2, 3})</step>
    <step
pause="0.05">UserMacros.RecallMacroById("Wiki.Macros.Cuelists.SetOption
.FFQ.0ff")</step>
  </sequence>
</macro>

</avolites.macros>

```

## Explanation


This explains the functional steps within the sequence. For all the other XML details please refer to [Formats and syntax](#)

tbd

## How to use it

1. [make this macro available](#)

tbd



From:  
<https://www.avosupport.de/wiki/> - **AVOSUPPORT**

Permanent link:  
<https://www.avosupport.de/wiki/macros/example/cuelistsetffq?rev=1623409627>

Last update: **2021/06/11 11:07**

