

Example

# Masters - Nudge Master Up/Down

<b>by:</b>	Alberto Faria Costa, May 2018
<b>published:</b>	<a href="http://forum.avolites.com/viewtopic.php?f=3&amp;p=20557">http://forum.avolites.com/viewtopic.php?f=3&amp;p=20557</a>
<b>description:</b>	Macros to nudge a master up/down

[nudge](#), [master](#)

## functions

- [Masters.NudgeUp](#)
- [Masters.NudgeDown](#)

For the available master's handleIds see [titanId](#)

## Code

[nudgeratemaster.xml](#)

```
<?xml version="1.0" encoding="utf-8"?>
<avolites.macros xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="Avolites.Menus.xsd">

  <!-- RATE MASTERS -->
  <!-- Rate Grand Master: titanid=1604 -->
  <!-- Rate Master 1: titanid=1608 -->
  <!-- Rate Master 2: titanid=1612 -->
  <!-- Rate Master 3: titanid=1616 -->
  <!-- Rate Master 4: titanid=1620 -->
  <!-- http://www.avosupport.de/wiki/macros:types:object:handle:titanid -
  ->
  <!-- Created by: Alberto Faria Costa -->

  <macro id="Avolites.Macros.RateMasterNudgeUp" name="RATE MASTER UP">
    <sequence>
      <step>Masters.NudgeUp(1604)</step>
    </sequence>
  </macro>

  <macro id="Avolites.Macros.RateMasterNudgeDown" name="RATE MASTER
DOWN">
    <sequence>
      <step>Masters.NudgeDown(1604)</step>
    </sequence>
  </macro>
```

```
<!-- add macros for the other masters here ... -->
```

```
</avolites.macros>
```

## Explanation

This explains the functional steps within the sequence. For all the other XML details please refer to [Formats and syntax](#)

The functions `Masters.NudgeUp()` and `Masters.NudgeDown()` are called for a specific master, identified by its titanId.

## How to use it

- [make this macro available](#)

From:

<https://www.avosupport.de/wiki/> - **AVOSUPPORT**

Permanent link:

<https://www.avosupport.de/wiki/macros/example/nudgemaster>

Last update: **2024/08/24 08:25**

