Example

# Nudge Master Up/Down

| | |
|---|---|
| **by:** | Alberto Faria Costa, May 2018 |
| **published:** | http://forum.avolites.com/viewtopic.php?f=3&p=20557 |
| **description:** | Macros to nudge a master up/down |

nudge, master

### functions

- Masters.NudgeUp
- Masters.NudgeDown

For the available master's handleIds see titanId

## Code

nudgeratemaster.xml

```
<?xml version="1.0" encoding="utf-8"?>
<avolites.macros xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="Avolites.Menus.xsd">

<!-- RATE MASTERS -->
<!-- Rate Grand Master: titanid=1604 -->
<!-- Rate Master 1: titanid=1608 -->
<!-- Rate Master 2: titanid=1612 -->
<!-- Rate Master 3: titanid=1616 -->
<!-- Rate Master 4: titanid=1620 -->
<!-- http://www.avolites.de/wiki/macros:types:object:handle:titanid -->
<!-- Created by: Alberto Faria Costa -->


  <macro id="Avolites.Macros.RateMasterNudgeUp" name="RATE MASTER UP">
    <sequence>
     <step>Masters.NudgeUp(1604)</step>
   </sequence>
 </macro>

  <macro id="Avolites.Macros.RateMasterNudgeDown" name="RATE MASTER
DOWN">
    <sequence>
    <step>Masters.NudgeDown(1604)</step>
   </sequence>
 </macro>
```

```
<!-- add macros for the other masters here ... -->


 </avolites.macros>
```

## Explanation

This explains the functional steps within the sequence. For all the other XML details please refer to Formats and syntax

The functions `Masters.NudgeUp()` and `Masters.NudgeDown()` are called for a specific master, identified by its titanId.

## How to use it

- make this macro available

tbd

From:
https://www.avosupport.de/wiki/ - **AVOSUPPORT**

Permanent link:
**https://www.avosupport.de/wiki/macros/example/nudgemaster?rev=1537103151**

Last update: **2018/09/16 13:05**