

Example

# Timecode - Toggle On/Off for particular playback

<b>by:</b>	Gregory Haynes, May 2016
<b>published:</b>	<a href="http://forum.avolites.com/viewtopic.php?f=20&amp;t=4517">http://forum.avolites.com/viewtopic.php?f=20&amp;t=4517</a>
<b>description:</b>	Toggle whether the cue list on handle 1 of the current page is enabled for timecode.
<b>remarks:</b>	The original idea was to toggle a cuelist which is identified by its legend - but that's not possible. Greg writes ' <i>I don't think there is a way to do this at the moment. I found a way of toggling a playback based on its location but it uses the current page, you could use the Playbacks window instead (which would be "PlaybackWindow").</i> '

[handle](#), [timecode](#), [toggle](#), [source](#)

## functions

- [Handles.SetSourceHandle](#)
- [Playbacks.Timecode.ToggleEnabled.Handle](#)
- [Handles.SetSourceHandleFromHandle](#)

## Code

[togglePbTimecode.xml](#)

```
<?xml version="1.0" encoding="utf-8"?>
<avolites.macros>
  <macro id="UserMacro.TogglePlaybackTimecode">
    <name>Toggle Timecode Enabled</name>
    <description>Toggle whether the cue list on handle 1 of the current
page is enabled for timecode.</description>
    <sequence>
      <step>Handles.SetSourceHandle("Playbacks", 0)</step>
<step>Playbacks.Timecode.ToggleEnabled.Handle(Handles.SourceHandle)</st
ep>
      <step>Handles.SetSourceHandleFromHandle(null)</step>
    </sequence>
  </macro>
</avolites.macros>
```

## Explanation

This explains the functional steps within the sequence. For all the other XML details please refer to [Formats and syntax](#)

- `Handles.SetSourceHandle("Playbacks", 0)` makes the playback 1 the source handle
- `Playbacks.Timecode.ToggleEnabled.Handle(Handles.SourceHandle)` toggles the `Timecode.Enabled` setting of this handle - this is the 'Connected Cuelists' toggle button in the Timecode menu
- `Handles.SetSourceHandleFromHandle(null)` empties the source handle property.

## How to use it

- [Make this macro available](#)-
- create a cuelist on playback 1
- open the [Timecode] menu
- go to [Connected Cue Lists] - the button [Cue List Playbacks[1]] is inactive
- <Exit> (the macro doesn't run as long as we are in this menu)
- fire the macro
- go to [Connected Cue Lists] - the button [Cue List Playbacks[1]] is now active

From:  
<https://www.avosupport.de/wiki/> - **AVOSUPPORT**

Permanent link:  
<https://www.avosupport.de/wiki/macros/example/playbacktoggletimecode>

Last update: **2019/01/15 02:20**

