Example

Set Autoload to Go on Target on a specific list

by:	Sebastian Beutel, March 2025
published:	here
description:	Create an autoload on the selected cuelist cue, pointing to a specific cuelist, with 'Press Go on Target'
remarks:	idea by Pontus Wallin in Facebook

It seems that currently (Titan 17/Titan 18) Autoloads with Go on Target release the target if not used in subsequent cues. This has been reported and will be fixed. Consider recording and using a macro instead (connect to other cuelist and hit Go, or press the other cuelist'S go button).

Cuelist, Autoload, GoOnTarget

functions

- Playbacks.Editor.SelectCueFromViewing
- Playbacks.Editor.Autoload.SetPlaybackAutoload
- Menu.ExitRootOrLatched

Code

SetAutoload.xml

```
<?xml version="1.0" encoding="utf-8"?>
<avolites.macros>
  <macro id="Wiki.Macros.SetAutoload.CL2Go" name="Set Autoload to CL2
Go">
    <sequence>
      <step>Playbacks.Editor.SelectCueFromViewing()</step>
<step>Playbacks.Editor.Autoload.SetPlaybackAutoload("cueListHandleUN=2"
, 2, 0)</step>
      <step>Menu.ExitRootOrLatched()</step>
    </sequence>
  </macro>
</avolites.macros>
```

Explanation

This explains the functional steps within the sequence. For all the other XML details please refer to

Formats and syntax

tbd

How to use it

1. make this macro available

tbd

From:
https://www.avosupport.de/wiki/ - **AVOSUPPORT**

Permanent link:
https://www.avosupport.de/wiki/macros/example/setautoloadgo?rev=1742585970

Last update: **2025/03/21 19:39**