

Example

# Set Autoload to Go on Target on a specific list

|                     |   |
|---------------------|---|
| <b>by:</b>          | Sebastian Beutel, March 2025  |
| <b>published:</b>   | here  |
| <b>description:</b> | Create an autoload on the selected cuelist cue, pointing to a specific cuelist, with 'Press Go on Target' |
| <b>remarks:</b>     | idea by Pontus Wallin in <a href="#">Facebook</a>   |

**It seems that currently (Titan 17/Titan 18) Autoloads with Go on Target release the target if not used in subsequent cues. This has been reported and will be fixed. Consider recording and using a macro instead (connect to other cuelist and hit Go, or press the other cuelist's go button).**

[Cuelist](#), [Autoload](#), [GoOnTarget](#)

## functions

- [Playbacks.Editor.SelectCueFromViewing](#)
- [Playbacks.Editor.Autoload.SetPlaybackAutoload](#)
- [Menu.ExitRootOrLatched](#)

## Code

[SetAutoload.xml](#)

```
<?xml version="1.0" encoding="utf-8"?>
<avolites.macros>
  <macro id="Wiki.Macros.SetAutoload.CL2Go" name="Set Autoload to CL2 Go">
    <sequence>
      <step>Playbacks.Editor.SelectCueFromViewing()</step>
      <step>Playbacks.Editor.Autoload.SetPlaybackAutoload("cueListHandleUN=2", 2, 0)</step>
      <step>Menu.ExitRootOrLatched()</step>
    </sequence>
  </macro>
</avolites.macros>
```

## Explanation

This explains the functional steps within the sequence. For all the other XML details please refer to

## Formats and syntax

tbd

## How to use it

1. [make this macro available](#)

tbd

From:

<https://www.avosupport.de/wiki/> - **AVOSUPPORT**

Permanent link:

<https://www.avosupport.de/wiki/macros/example/setautoloadgo?rev=1742586010>

Last update: **2025/03/21 19:40**

