

Example

Set a playback's key profile

| | |
|---------------------|---|
| by: | Kim Wida, Feb 2018 |
| published: | http://forum.avolites.com/viewtopic.php?f=20&t=5553 |
| description: | Set a playback's key profile |
| remarks: | |

[\[playback, profile\]](#)

functions

- [Profiles.AssignHandleProfile](#)
- [Profiles.GetHandleProfileId](#)

identifiers

- [profileId](#)

Code

[setProfile.xml](#)

```
<?xml version="1.0" encoding="utf-8"?>
<avolites.macros xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="Avolites.Menus.xsd">
  <macro name="Set Key Profile to UN11047"
id="Wiki.Macros.SetplaybackProfile">
    <sequence>
      <step>Profiles.AssignHandleProfile(handle:"chaseHandleUN=10555",
Profiles.GetHandleProfileId(handle:"chaseHandleUN=11047"))</step>
    </sequence>
  </macro>

  <macro name="Set Key Profile of chaser 5563"
id="Wiki.Macros.SetplaybackProfile.Ex1">
    <sequence>
<step>Profiles.AssignHandleProfile(handle:"chaseHandleUN=5963",493461)<
/step>
    </sequence>
  </macro>

</avolites.macros>
```

Explanation

This explains the functional steps within the sequence. For all the other XML details please refer to [Formats and syntax](#)

As the [Profile IDs](#) of user-defined key profiles are random, the first example might be much more useful than the second: it sets the key profile of one playback to the key profile of another playback:

- `Profiles.GetHandleProfileId(handle:"chaseHandleUN=11047")` retrieves the profile id of the playback with user number 11047.
- `Profiles.AssignHandleProfile(handle:"chaseHandleUN=10555", ...)` assigns this as profile id for another playback

The second example directly sets a profile id - however, as the correct ID cannot be predicted, you'd need to find the correct id e.g. with [this example](#) and manually enter the number in the macro - not very handy.

How to use it

1. [make this macro available](#)
2. create a chaser with #11047 as dummy playback and set its key profile.
3. in order to apply this to another chaser re-legend that other chaser to #10555 and fire the macro

The second macro is merely for documentation purposes - you'd need to edit it to match the profile id of your show.

From:
<https://www.avosupport.de/wiki/> - **AVOSUPPORT**

Permanent link:
<https://www.avosupport.de/wiki/macros/example/setplaybackprofile?rev=1529935669>

Last update: **2018/06/25 14:07**

