

Function

Handles.SetGroupName

```
Void Handles.SetGroupName(String group, String name)
```

API	http://api.avolites.com/11.0/Handles.SetGroupName.html
description	Sets the name of the current page of a group.
namespace	Handles
parameter	group (String) : Name of the group, see Location name (String) : The string for the new page name.
return value	Void

When using characters outside the ASCII character table as name the results may vary:

- in order to get an ampersand (the & character) you must write it as entity (&#amp;):
Handles.SetGroupName("Colours", "Greens &#amp; Blues")
- german Umlauts (ä, ö, ü, ß and the like) work normally (entities would throw errors):
Handles.SetGroupName("Colours", "Grün")
- you can even display UTF-16 characters by using the HTML code notation, e.g. for the Yuan character <html>元</html>:
Handles.SetGroupName("Playbacks", "元")

Example in

[Legend - Set a Page Legend](#):

```
<step>Handles.SetGroupName("Fixtures", "Washes")</step>
```

Also used in

- [Legend - Set a Page Legend](#)
- [Function list](#)

Remarks

From:
<https://www.avosupport.de/wiki/> - **AVOSUPPORT**

Permanent link:
<https://www.avosupport.de/wiki/macros/function/handles.setgrouppagename>

Last update: **2018/08/26 09:59**

