

Function

Handles.SetSourceHandle

```
Void Handles.SetSourceHandle(String group, Int32 index)
```

API	http://api.avolites.com/10.1/Handles.SetSourceHandle.html
description	Set the source handle to a specific group and index. Updates the context info
namespace	Handles
parameter	group (String) : group of handles index (Int32) : number of playback in specified group
return value	Void
affects	Handles.SourceHandle

See [Identifiers](#) for available groups of handles.

This always refers to the current page of the group. In order to select a handle on any page see [Handles.SetSourceHandleFromHandle](#)

Example in

[Timecode - Toggle On/Off for particular playback:](#)

```
<step>Handles.SetSourceHandle("Playbacks", 0)</step>
```

Sets source handle to be handle #1 of the current playbacks page.

Also used in

- [Create Workspaces](#)
- [Delete Workspace X](#)
- [Change Playback Timings Grid](#)
- [Move \(Copy\) Handle](#)
- [Store cues with current page names as legends](#)
- [Programmer - Park/Restore/Swop](#)
- [Timecode - Toggle On/Off for particular playback](#)
- [Playback - Record and set userNumber](#)
- [Legend - Set an icon as legend](#)
- [Playback - Set fade-in time - modular](#)
- [Playback - Set fade-out time](#)
- [Playback - Set lock state](#)
- [Function list](#)
- [Handles.SetSourceHandleFromHandle](#)
- [Handles](#)

Last update:
2018/09/16 12:26

macros:function:handles.setsourcehandle <https://www.avosupport.de/wiki/macros/function/handles.setsourcehandle>

Remarks

From:

<https://www.avosupport.de/wiki/> - **AVOSUPPORT**

Permanent link:

<https://www.avosupport.de/wiki/macros/function/handles.setsourcehandle>

Last update: **2018/09/16 12:26**

