

Function

Timecode.TimecodeOne.SetSource

Nowadays there are four timecodes available in Titan, and the same functions are available for [Timecode.TimecodeTwo](#), [Timecode.TimecodeThree](#) and [Timecode.TimecodeFour](#).

```
Void Timecode.TimecodeOne.SetSource(AcwTimecodeSource source)
```

API	https://api.avolites.com/11.0/Timecode.TimecodeOne.Pause.html
description	Sets the active timer source in Titan.
namespace	Timecode.TimecodeOne
parameter	source (AcwTimecodeSource)
return value	Void

Example in

[Timecode - Winamp Tracks](#):

```
<step>ActionScript.SetProperty.Enum("Timecode.TimecodeTwo.Source",  
"Winamp")</step>  
<step  
pause="0.05">Timecode.TimecodeTwo.SetSource(Timecode.TimecodeTwo.Source)</st  
ep>
```

The first step sets the property [Timecode.TimecodeTwo.Source](#) to "Winamp". The second step then puts this into the timecode itself

Also used in

- [Timecode - Set starttime to livetime and toggle source](#)
- [Timecode - Winamp Tracks](#)

Remarks

From:
<https://www.avosupport.de/wiki/> - **AVOSUPPORT**

Permanent link:
<https://www.avosupport.de/wiki/macros/function/timecode.timecodeone.setsource>

Last update: **2020/03/28 21:29**

