

Function

# Timelines.ImportMarkersFromString

```
Void Timelines.ImportMarkersFromString(Int32 timelineId, String importMappingVersion, String csvFilePath, AcwFrameRate frameRate)
```

<b>API</b>	<a href="https://api.avolites.com/16.0/api/Timelines.ImportMarkersFromString.html">https://api.avolites.com/16.0/api/Timelines.ImportMarkersFromString.html</a>
<b>description</b>	Imports markers into the timeline.
<b>namespace</b>	Timelines
<b>parameter</b>	timelineId ( <a href="#">Int32</a> ): The timeline ID.
	importMappingVersion ( <a href="#">String</a> ): The XML node for the version of the mapping to use.
	csvFilePath ( <a href="#">String</a> ): The csv file path.
	frameRate ( <a href="#">AcwFrameRate</a> ): The framerate to import.
<b>return value</b>	<a href="#">Void</a>

## Example in

[Timeline: Import Markers:](#)

```
<step>Timelines.ImportMarkersFromString(  
    Handles.GetTitanIdFromHandle("timelineHandleUN=1"),  
    "&lt;Version /&gt;",  
    "C:\Users\sb\Documents\Titan\Markers\test.csv",  
    Timecode.ParseFrameRate(100))  
</step>
```

## Also used in

- [Timeline: Import Markers](#)

## Remarks

From:  
<https://www.avosupport.de/wiki/> - AVOSUPPORT

Permanent link:  
<https://www.avosupport.de/wiki/macros/function/timelines.importmarkersfromstring?rev=1680514810>

Last update: 2023/04/03 09:40

