Function

Timelines.ImportMarkersFromString

```
Void Timelines.ImportMarkersFromString(
  Int32 timelineId,
  String importMappingVersion,
  String csvFilePath,
  AcwFrameRate frameRate
)
```

API	https://api.avolites.com/16.0/api/Timelines.ImportMarkersFromString.html
description	Imports markers into the timeline.
namespace	Timelines
parameter	timelineId (Int32): The timeline ID.
	importMappingVersion (String): The XML node for the version of the mapping to use.
	csvFilePath (String): The csv file path.
	frameRate (AcwFrameRate): The framerate to import.
return value	Void

Arguments

- **timelineId** is the identifier or the timeline you want to import the markers into. Unlike for other functions which expect a handle this one expects a titanId. You may retrieve this e.g. from Web API, or you use e.g. Handles.GetTitanIdFromHandle to get the titanId for a specific handle by its usernumber:
  - `Timelines.ImportMarkersFromString(1819, …)` – example with hardcoded titanId
  - `Timelines.ImportMarkersFromString(Handles.GetTitanIdFromHandle("timelineHandleUN=1"), …)` – example to get the titanId from a usernumber

Example in

Timeline: Import Markers:

```
<step>Timelines.ImportMarkersFromString(
  Handles.GetTitanIdFromHandle("timelineHandleUN=1"),
  "&lt;Version /&gt;",
  "C:\Users\sb\Documents\Titan\Markers\test.csv",
  Timecode.ParseFrameRate(100))
</step>
```

Also used in

- Timeline: Import Markers

Remarks

From:
https://www.avosupport.de/wiki/ - **AVOSUPPORT**

Permanent link:
https://www.avosupport.de/wiki/macros/function/timelines.importmarkersfromstring?rev=1680515881

Last update: **2023/04/03 09:58**