

Function

# Timelines.ImportMarkersFromString

```
Void Timelines.ImportMarkersFromString(  
    Int32 timelineId,  
    String importMappingVersion,  
    String csvFilePath,  
    AcwFrameRate frameRate  
)
```

<b>API</b>	<a href="https://api.avolites.com/16.0/api/Timelines.ImportMarkersFromString.html">https://api.avolites.com/16.0/api/Timelines.ImportMarkersFromString.html</a>
<b>description</b>	Imports markers into the timeline.
<b>namespace</b>	Timelines
<b>parameter</b>	timelineId ( <a href="#">Int32</a> ): The timeline ID.
	importMappingVersion ( <a href="#">String</a> ): The XML node for the version of the mapping to use.
	csvFilePath ( <a href="#">String</a> ): The csv file path.
	frameRate ( <a href="#">AcwFrameRate</a> ): The framerate to import.
<b>return value</b>	<a href="#">Void</a>

## Arguments

- **timelineId** is the identifier or the timeline you want to import the markers into. Unlike for other functions which expect a [handle](#) this one expects a [titanId](#). You may retrieve this e.g. from Web API, or you use e.g. [Handles.GetTitanIdFromHandle](#) to get the titanId for a specific handle by its usernumber:
  - `Timelines.ImportMarkersFromString(1819, ...)` - example with hardcoded titanId
  - `Timelines.ImportMarkersFromString(Handles.GetTitanIdFromHandle("timelineHandleUN=1"), ...)` - example to get the titanId from a usernumber

## Example in

[Timeline: Import Markers:](#)

```
<step>Timelines.ImportMarkersFromString(  
    Handles.GetTitanIdFromHandle("timelineHandleUN=1"),  
    "&lt;Version /&gt;",  
    "C:\Users\sB\Documents\Titan\Markers\test.csv",  
    Timecode.ParseFrameRate(100))  
</step>
```

## Also used in

- [Timeline: Import Markers](#)

## Remarks

From:  
<https://www.avosupport.de/wiki/> - AVOSUPPORT

Permanent link:  
<https://www.avosupport.de/wiki/macros/function/timelines.importmarkersfromstring?rev=1680515881>

Last update: **2023/04/03 09:58**

