Web API example

Set Timecode Start from Palette fade

Set the Timecode start time for versions pre Titan v14. The challenge is that this reqires a TimecodeTime object but the required cast was only implemented in Titan v14. The workaround is to set the palette fade time (as you would do by simply entering a number) and then call a macro which uses this to set the timecode start time.

For versions from Titan v14 on you can directly set the Timecode starttime using Timecode.TimecodeOne.SetStartTime.

author, date	Gregory Haynes, February 2022
published	https://www.avolites.de/downloads/icke_siegen/SetTcStartTime/
prog. lang./ framework	HTML, JS, CSS; none (wrote everything with a text editor)
description	set the palette fade time, then call a macro to transfer this into timecode start time
other requirements	a way to issue POST requests, e.g. RestMan for Chrome

Screenshots

1. use RestMan (or another way to output a Post request) to set the palette fadetime



2. call a macro (here: Timecode - Set Start Time from Palette Fade to use the value as Timecode start

time)



In order to call a macro via WebAPI it needs to be in the show library AND needs to be copied/moved to a handle.

3. the little html page at https://www.avolites.de/downloads/icke_siegen/SetTcStartTime/:



How it works

`Set Numeric Value` the value from the adjacent input field and sends it to Titan as numeric value (as like as used to set a palette fade time).

`Set 0`, `Set 1`, `Set 5` send some predefined values.

`Set TC1 Start` fires the macro to use the numeric value as timecode 1 start time.

Remember to download and deploy the macro Timecode - Set Start Time from Palette Fade.

API Requests

- InputValue
- Run

From:
https://www.avosupport.de/wiki/ - **AVOSUPPORT**

Permanent link:
https://www.avosupport.de/wiki/webapi/examples/settimecodefrompalettefade?rev=1643981901

Last update: **2022/02/04 13:38**